

LV432454

Earth-leakage add-on protection module,
ComPact NSX 400/630, MB type, 440 VAC to
550 VAC, 300 mA to 30 A, 4 poles



Main

Range of product	ComPact NSX400...630
Range	ComPact
Product or component type	Vigi add-on
Device application	Wiring
Range compatibility	ComPact NSX400 circuit breaker ComPact NSX630 circuit breaker
Poles description	4P
[In] rated current	400 A 630 A
Earth-leakage add-on module name	MB
Earth-leakage protection class	Class A
Residual earth-leakage sensitivity adjustment type	Adjustable 5 settings
Earth-leakage sensitivity	0.3 A 1 A 3 A 10 A 30 A
Residual earth-leakage time delay adjustment type	Adjustable 4 settings
[Δt] residual earth-leakage time delay adjustment	60 Ms 150 Ms 310 Ms 0 ms

Complementary

Network type	AC
Network frequency	50/60 Hz
[Ue] rated operational voltage	440...550 V AC 50/60 Hz conforming to IEC 60947-2
Earth-leakage protection	With
Maximum breaking time	800 ms
Overvoltage category	Class II

Environment

Electrical shock protection class	Class II
Standards	IEC 60947-2

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	3.337 kg
Package 1 Height	14 cm
Package 1 width	16.8 cm
Package 1 Length	19.7 cm
Unit Type of Package 2	S04

Number of Units in Package 2	6
Package 2 Weight	20.788 kg
Package 2 Height	30 cm
Package 2 width	40 cm
Package 2 Length	60 cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------