



### Main

|                           |                                  |
|---------------------------|----------------------------------|
| Device short name         | CT module and voltage output     |
| Product or component type | Current transformer              |
| Device application        | Control                          |
| Range compatibility       | ComPact NSX400<br>ComPact NSX630 |
| Poles description         | 3P                               |
| [In] rated current        | 400 A                            |
| Current transformer ratio | 400/5 A                          |
| Power consumption in VA   | 2 VA                             |
| Accuracy class            | Class 0.5                        |

### Complementary

|                                |                                     |
|--------------------------------|-------------------------------------|
| [Ue] rated operational voltage | 530 V                               |
| Network type                   | AC                                  |
| Network frequency              | 50/60 Hz                            |
| Auxiliary connection terminal  | Cable connector 2.5 mm <sup>2</sup> |

### Environment

|                                   |                              |
|-----------------------------------|------------------------------|
| Electrical shock protection class | Class II                     |
| IP degree of protection           | IP40 conforming to IEC 60529 |
| IK degree of protection           | IK04 conforming to IEC 62262 |

### Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Weight             | 2.16 kg  |
| Package 1 Height             | 13 cm    |
| Package 1 width              | 15 cm    |
| Package 1 Length             | 20 cm    |
| Unit Type of Package 2       | S03      |
| Number of Units in Package 2 | 2        |
| Package 2 Weight             | 4.807 kg |
| Package 2 Height             | 30 cm    |
| Package 2 width              | 30 cm    |
| Package 2 Length             | 40 cm    |

### Offer Sustainability

|                            |   |
|----------------------------|---|
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>                           |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>        |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a> |
| Circularity Profile        | <a href="#">End Of Life Information</a>       |

## Contractual warranty

---

Warranty

18 months

---