

Product data sheet

Characteristics

LV432862

current transformer module with voltage output,
ComPact NSX630, 600 A rating, 4 poles



Main

Device short name	CT module and voltage output
Product or component type	Current transformer
Device application	Control
Range compatibility	ComPact NSX630 Compact INS Compact INV
Poles description	4P
[In] rated current	600 A
Current transformer ratio	600/5 A
Power consumption in VA	2 VA
Accuracy class	Class 0.5

Complementary

[Ue] rated operational voltage	530 V
Network type	AC
Network frequency	50/60 Hz
Auxiliary connection terminal	Cable connector 2.5 mm ²

Environment

Electrical shock protection class	Class II
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK04 conforming to IEC 62262

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	2.655 kg
Package 1 Height	14 cm
Package 1 width	17 cm
Package 1 Length	20 cm
Unit Type of Package 2	S03
Number of Units in Package 2	2
Package 2 Weight	5.797 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes

China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------
