



### Main

Range	ComPact
Range of product	ComPact NSX100...250 ComPact NSX100...250 DC
Product or component type	Trip unit
Trip unit name	TM-G
Trip unit technology	Thermal-magnetic
Range compatibility	ComPact NSX100 ComPact NSX160 ComPact NSX100 DC
Device application	Generator
Number of poles	4P
Protected poles description	4t
Neutral position	Left
Trip unit protection functions	LI
Protection type	L : for overload protection (thermal) I : for short-circuit protection (magnetic)
Trip unit rated current	63 A at 40 °C
[Ue] rated operational voltage	690 V AC 50/60 Hz 750 V DC
Network type	DC AC
Network frequency	50/60 Hz

### Complementary

Long-time pick-up adjustment type Ir (thermal protection)	Adjustable
[Ir] long-time protection pick-up adjustment range	0.7...1 x In
Long-time protection delay adjustment type tr	Fixed
[tr] long-time protection delay adjustment range	120...400 s at 1.5 x In
Short-time protection pick-up adjustment type Isd	Fixed
[Isd] Short-time protection pick-up adjustment range	125 A
Short-time protection delay adjustment type tsd	Fixed
Earth-leakage protection	Without
Neutral protection settings	1 x Ir (4t)

### Environment

Standards	UL 508 EN/IEC 60947-2
Product certifications	Marine CCC EAC
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	582 g
Package 1 Height	6.7 cm
Package 1 width	9.8 cm
Package 1 Length	15 cm
Unit Type of Package 2	S03
Number of Units in Package 2	23
Package 2 Weight	13.873 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------