



Main

Range	ComPact
Range of product	ComPact NSX100...250
Product or component type	Trip unit
Trip unit name	Micrologic 6.2 E-M
Trip unit technology	Electronic
Range compatibility	ComPact NSX160 ComPact NSX250
Device application	Motor
Number of poles	3P
Protected poles description	3t
Trip unit protection functions	LSIG
Protection type	L : for overload protection (long time) S : for short time short-circuit protection I : for instantaneous short-circuit protection G : for ground fault protection
Trip unit rated current	150 A at 65 °C
[Ue] rated operational voltage	690 V AC 50/60 Hz
Network type	AC
Network frequency	50/60 Hz

Complementary

Motor tripping class	10 30 5 20
Complementary motor protection	Protracted starting time Stalled rotor Current unbalance Underload
Long-time pick-up adjustment type I _r (thermal protection)	Adjustable 9 settings
[I _r] long-time protection pick-up adjustment range	70...150 A
Long-time protection delay adjustment type t _r	Adjustable
[t _r] long-time protection delay adjustment range	120 S at 1.5 x I _r for trip class 5 6.5 S at 6 x I _r for trip class 5 5 S at 7.2 x I _r for trip class 5 240 S at 1.5 x I _r for trip class 10 13.5 S at 6 x I _r for trip class 10 10 S at 7.2 x I _r for trip class 10 480 S at 1.5 x I _r for trip class 20 26 S at 6 x I _r for trip class 20 20 S at 7.2 x I _r for trip class 20 720 S at 1.5 x I _r for trip class 30 38 S at 6 x I _r for trip class 30 30 s at 7.2 x I _r for trip class 30
Thermal memory	20 minutes before and after tripping
Short-time protection pick-up adjustment type I _{sd}	Adjustable 9 settings
[I _{sd}] Short-time protection pick-up adjustment range	5...13 x I _r
Short-time protection delay adjustment type t _{sd}	Fixed

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

[tsd] Short-time protection delay adjustment range	0.01 s
Instantaneous protection pick-up adjustment type li	Fixed
[li] instantaneous protection pick-up adjustment range	2250 A
Ground-fault protection pick-up adjustment type lg	Adjustable
[lg] ground-fault protection pick-up adjustment range	0.2...1 x In for In > 50 A 0.3...1 x In for In = 50 A 0.6...1 x In for In = 25 A lg enable on/off
Ground-fault protection time delay adjustment type tg	Adjustable
[tg] ground-fault protection time delay adjustment range	0...0.4 s
Earth-leakage protection	Without
Zone selective interlocking ZSI	With
Local signalling	Flashing LED (green) for ready to operate LED 95 % lth (red) for temperature over set point
Display type	LCD display
Type of measurement	Energy meter
Electrical data recording	Maintenance indicators

Environment

Standards	EN/IEC 60947-2 UL 508
Product certifications	Marine CCC EAC
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	544 g
Package 1 Height	9.6 cm
Package 1 width	11 cm
Package 1 Length	15.3 cm
Unit Type of Package 2	S03
Number of Units in Package 2	11
Package 2 Weight	6.471 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------