

LV433549

circuit breaker ComPact NSX250HB1, 75 kA at 690 VAC, MicroLogic 5.2 E trip unit 100 A, 4 poles 4d



Main

| | |
|--|--|
| Range | ComPact |
| Product name | ComPact NSX |
| Range of product | ComPact NSX100...250 |
| Device short name | NSX250HB1 |
| Product or component type | Circuit breaker |
| Device application | Distribution |
| Number of poles | 4P |
| Protected poles description | 4t 3t + N/2 3t + OSN 3t |
| Neutral position | Left |
| [In] rated current | 100 A at 40 °C |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz |
| Network type | AC |
| Network frequency | 50/60 Hz |
| Suitability for isolation | Yes conforming to EN/IEC 60947-2 |
| Utilisation category | Category A |
| [Icu] rated ultimate short-circuit breaking capacity | 85 KA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2 80 KA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2 75 KA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Performance level | HB1 75 kA 690 V AC |
| Trip unit name | Micrologic 5.2 E |
| Trip unit technology | Electronic |
| Trip unit protection functions | LSI |
| Control type | Toggle |
| Circuit breaker mounting mode | Fixed |

Complementary

| | |
|---|--|
| [Ui] rated insulation voltage | 800 V AC 50/60 Hz |
| [Uimp] rated impulse withstand voltage | 8 kV |
| [Ics] rated service short-circuit breaking capacity | 85 KA at 500 V AC 50/60 Hz conforming to IEC 60947-2 80 KA at 525 V AC 50/60 Hz conforming to IEC 60947-2 75 KA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Mechanical durability | 20000 cycles |
| Electrical durability | 5000 Cycles at 690 V In 10000 Cycles at 690 V In/2 10000 Cycles at 440 V In 20000 cycles at 440 V In/2 |
| Mounting support | Backplate |
| Upside connection | Front |
| Downside connection | Front |
| Connection pitch | 35 mm |

| | |
|---|--|
| Protection type | L : for overload protection (long time) S : for short time short-circuit protection I : for instantaneous short-circuit protection |
| Trip unit rating | 100 A at 40 °C |
| Long-time pick-up adjustment type I _r (thermal protection) | Adjustable 9 settings |
| [I _r] long-time protection pick-up adjustment range | 40...100 A |
| Long-time protection delay adjustment type t _r | Adjustable |
| [t _r] long-time protection delay adjustment range | 15...400 S at 1.5 x I _r 0.35...11 S at 7.2 x I _r 0.5...16 s at 6 x I _r |
| Thermal memory | 20 minutes before and after tripping |
| Short-time protection pick-up adjustment type I _{sd} | Adjustable 9 settings |
| [I _{sd}] Short-time protection pick-up adjustment range | 1.5...10 x I _r |
| Short-time protection delay adjustment type t _{sd} | Adjustable |
| [t _{sd}] Short-time protection delay adjustment range | 0...0.4 s |
| Instantaneous protection pick-up adjustment type I _i | Adjustable |
| [I _i] instantaneous protection pick-up adjustment range | 1.5...15 x I _n |
| Earth-leakage protection | Without |
| Neutral protection settings | 0.5 x I _r (3t + N/2) 1 x I _r (4t) 1.6 x I _r (3t + OSN) No protection (3t) |
| Zone selective interlocking ZSI | With |
| Number of slots for electrical auxiliaries | 5 slot(s) |
| Local signalling | Flashing LED (green) for ready to operate LED 105 % I _r (red) for overload LED 90 % I _r (orange) for overload |
| Display type | LCD display |
| Type of measurement | Energy meter |
| Communication of data | Power quality Instantaneous and demand values Maximeters/Minimeters Maintenance indicators Protection and alarm settings Time-stamped histories and event tables Energy metering Demand current and power |
| Width (W) | 140 mm |
| Height (H) | 161 mm |
| Depth (D) | 86 mm |
| Net weight | 2.8 kg |

Environment

| | |
|---------------------------------------|--|
| Standards | EN/IEC 60947 |
| Product certifications | EAC CCC Marine |
| Overvoltage category | Class II |
| Electrical shock protection class | Class II |
| Pollution degree | 3 conforming to IEC 60664-1 |
| IP degree of protection | IP40 conforming to IEC 60529 |
| IK degree of protection | IK07 conforming to IEC 62262 |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...85 °C |
| Relative humidity | 0...95 % |
| Operating altitude | 0...2000 m without derating 2000 m...5000 m with derating |

Packing Units

| | |
|------------------|-----------|
| Package 1 Weight | 2.800 kg |
| Package 1 Height | 13.500 cm |
| Package 1 width | 14.100 cm |
| Package 1 Length | 19.200 cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|