



## Main

|  |  |
|--|--|
| Range  | ComPact  |
| Product name   | ComPact NSX  |
| Range of product                                     | ComPact NSX100...250   |
| Device short name                                    | VigiCompact NSX250B  |
| Product or component type                            | Earth leakage circuit breaker  |
| Device application                                   | Distribution   |
| Number of poles                                      | 4P   |
| Protected poles description                          | 4t<br>3t<br>3t + N/2   |
| Neutral position                                     | Left   |
| [In] rated current                                   | 160 A at 40 °C   |
| [Ue] rated operational voltage                       | 440 V AC 50/60 Hz  |
| Network type   | AC   |
| Network frequency                                    | 50/60 Hz   |
| Suitability for isolation                            | Yes conforming to EN/IEC 60947-2   |
| Utilisation category                                 | Category A   |
| [Icu] rated ultimate short-circuit breaking capacity | 20 KA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>25 KA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2<br>40 kA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 |
| Performance level                                    | B 25 kA 415 V AC   |
| Trip unit name                                       | Micrologic 4.2   |
| Trip unit technology                                 | Electronic   |
| Trip unit protection functions                       | LSolR  |
| Control type   | Toggle   |
| Circuit breaker mounting mode                        | Fixed  |

## Complementary

|   |  |
|---|--|
| [Ui] rated insulation voltage                       | 500 V AC 50/60 Hz  |
| [Uimp] rated impulse withstand voltage              | 8 kV   |
| [Ics] rated service short-circuit breaking capacity | 40 KA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2<br>25 KA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2<br>20 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 |
| Mechanical durability                               | 20000 cycles   |
| Electrical durability                               | 10000 Cycles at 440 V In<br>20000 cycles at 440 V In/2   |
| Mounting support                                    | Backplate  |
| Upside connection                                   | Front  |
| Downside connection                                 | Front  |
| Connection pitch                                    | 35 mm  |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|   |  |
|---|--|
| Protection type   | L : for overload protection (long time)<br>So : for short time short-circuit protection with fixed delay<br>I : for instantaneous short-circuit protection<br>R : for earth-leakage protection |
| Trip unit rating  | 160 A at 40 °C   |
| Long-time pick-up adjustment type I <sub>r</sub> (thermal protection) | Adjustable 9 settings  |
| [I <sub>r</sub> ] long-time protection pick-up adjustment range       | 63...160 A   |
| Long-time protection delay adjustment type t <sub>r</sub>             | Fixed  |
| [t <sub>r</sub> ] long-time protection delay adjustment range         | 11 S at 7.2 x I <sub>r</sub><br>16 S at 6 x I <sub>r</sub><br>400 s at 1.5 x I <sub>r</sub>  |
| Thermal memory  | 20 minutes before and after tripping   |
| Short-time protection pick-up adjustment type I <sub>sd</sub>         | Adjustable   |
| [I <sub>sd</sub> ] Short-time protection pick-up adjustment range     | 1.5...10 x I <sub>r</sub>  |
| Short-time protection delay adjustment type t <sub>sd</sub>           | Fixed  |
| [t <sub>sd</sub> ] Short-time protection delay adjustment range       | 0.02 s   |
| Instantaneous protection pick-up adjustment type I <sub>i</sub>       | Fixed  |
| [I <sub>i</sub> ] instantaneous protection pick-up adjustment range   | 2400 A   |
| Earth-leakage protection  | Integrated   |
| Earth-leakage protection class  | Class A  |
| Earth-leakage protection sensitivity adjustment type IΔn              | Adjustable   |
| [IΔn] earth-leakage protection sensitivity adjustment range           | 30 MA<br>100 MA<br>300 MA<br>500 MA<br>1 A<br>3 A<br>5 A   |
| Earth-leakage protection specific mode                                | OFF using the IΔn rotary switch  |
| Earth-leakage protection time delay adjustment type Δt                | Adjustable   |
| [Δt] Earth-leakage protection time delay adjustment range             | 0 Ms<br>60 Ms<br>150 Ms<br>500 Ms<br>1 s   |
| Neutral protection settings   | 0.5 x I <sub>r</sub> (3t + N/2)<br>1 x I <sub>r</sub> (4t)<br>No protection (3t)   |
| Number of slots for electrical auxiliaries                            | 5 slot(s)  |
| Local signalling  | Flashing LED (green) for ready to operate<br>LED 105 % I <sub>r</sub> (red) for overload<br>LED 90 % I <sub>r</sub> (orange) for overload  |
| Width (W)   | 140 mm   |
| Height (H)  | 161 mm   |
| Depth (D)   | 86 mm  |
| Net weight  | 2.4 kg   |

## Environment

|                                       |                              |
|---------------------------------------|------------------------------|
| Standards                             | EN/IEC 60947                 |
| Product certifications                | CCC<br>EAC<br>Marine         |
| Overvoltage category                  | Class II                     |
| Electrical shock protection class     | Class II                     |
| Pollution degree                      | 3 conforming to IEC 60664-1  |
| IP degree of protection               | IP40 conforming to IEC 60529 |
| IK degree of protection               | IK07 conforming to IEC 62262 |
| Ambient air temperature for operation | -25...70 °C                  |
| Ambient air temperature for storage   | -40...85 °C                  |

|                    |  |
|--------------------|--|
| Relative humidity  | 0...95 %   |
| Operating altitude | 0...2000 m without derating<br>2000 m...5000 m with derating |

### Packing Units

|                  |            |
|------------------|------------|
| Package 1 Weight | 3.100 kg   |
| Package 1 Height | 126.000 mm |
| Package 1 width  | 161.000 mm |
| Package 1 Length | 140.000 mm |

### Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a>   |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>  |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        | <a href="#">End Of Life Information</a>   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| PVC free                   | Yes   |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|