



Main

Range of product	NG125
Range	Acti 9
Product name	Acti 9 NG125
Product or component type	Miniature circuit-breaker
Device short name	NG125L
Device application	Distribution
Poles description	2P
Number of protected poles	2
Neutral position	Left
[In] rated current	50 A at 40 °C
Network type	AC DC
Trip unit technology	Thermal-magnetic
Curve code	B
Breaking capacity	100 KA Icu at 220...240 V AC 50/60 Hz conforming to EN/IEC 60947-2 40 KA Icu at 440 V AC 50/60 Hz conforming to EN/IEC 60947-2 50 KA Icu at 380...415 V AC 50/60 Hz conforming to EN/IEC 60947-2 15 KA Icu at 500 V AC 50/60 Hz conforming to EN/IEC 60947-2 36 kA Icu at ≤ 250 V DC conforming to EN/IEC 60947-2
Utilisation category	Category A conforming to IEC 60947-2
Suitability for isolation	Yes conforming to IEC 60947-2

Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	380...415 V AC 50/60 Hz 500 V AC 50/60 Hz 220...240 V AC 50/60 Hz 440 V AC 50/60 Hz ≤ 250 V DC
Magnetic tripping limit	4 x In
[Ics] rated service breaking capacity	75 KA 75 % conforming to EN/IEC 60947-2 - 220...240 V AC 50/60 Hz 37.5 KA 75 % conforming to EN/IEC 60947-2 - 380...415 V AC 50/60 Hz 30 KA 75 % conforming to EN/IEC 60947-2 - 440 V AC 50/60 Hz 11.25 KA 75 % conforming to EN/IEC 60947-2 - 500 V AC 50/60 Hz 50 kA 100 % conforming to EN/IEC 60947-2 - 250 V DC
[Ui] rated insulation voltage	690 V AC 50/60 Hz conforming to EN/IEC 60947-2
[Uimp] rated impulse withstand voltage	8 kV conforming to EN/IEC 60947-2
Contact position indicator	Yes
Control type	Manual tripping test Toggle
Local signalling	Trip indicator ON/OFF indication
Mounting mode	Clip-on
Mounting support	35 mm symmetrical DIN rail
Comb busbar and distribution block compatibility	YES
9 mm pitches	6

Height	103 mm
Width	54 mm
Depth	81 mm
Net weight	0.48 kg
Mechanical durability	20000 cycles
Electrical durability	10000 cycles
Provision for padlocking	Padlockable
Locking options description	Integrated padlocking
Connections - terminals	Tunnel type terminals 1.5...50 mm ² rigid Tunnel type terminals 1...35 mm ² flexible
Wire stripping length	20 mm
Tightening torque	3.5 N.m
Earth-leakage protection	Separate block

Environment

Standards	EN/IEC 60947-2
IP degree of protection	IP20 conforming to IEC 60529
IK degree of protection	IK05 conforming to EN/IEC 62262
Pollution degree	3 conforming to IEC 60947-2
Overvoltage category	IV
Tropicalisation	2 conforming to IEC 60068-1
Relative humidity	95 % at 55 °C
Operating altitude	2000 m
Ambient air temperature for operation	-30...70 °C
Ambient air temperature for storage	-40...70 °C

Packing Units

Package 1 Weight	0.477 kg
Package 1 Height	0.800 dm
Package 1 width	0.550 dm
Package 1 Length	1.100 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------