



Main

Circuit breaker application	Distribution
Range	Acti 9
Product or component type	Earth leakage circuit breaker
Product name	DPN Vigi
Device short name	DPN N Vigi
Poles description	1P + N
Neutral position	Left
Number of protected poles	1
[In] rated current	10 A at 30 °C
Network type	AC
Trip unit technology	Thermal-magnetic
Curve code	C
Earth-leakage sensitivity	30 mA
Earth-leakage protection time delay	Instantaneous
Type	Type A-SI (Super Immunised)
Breaking capacity	6000 A Icn at 230 V AC conforming to EN 61009

Complementary

Device location in system	Outgoer
[Ue] rated operational voltage	230 V AC
Magnetic tripping limit	5...10 x In
Residual current tripping technology	Voltage independent
[Ics] rated service breaking capacity	6000 A at 230 V AC 50/60 Hz conforming to EN 61009
Limitation class	3 conforming to EN 61009
[Ui] rated insulation voltage	400 V AC conforming to EN 61009
[Uimp] rated impulse withstand voltage	4 kV conforming to EN 61009
Contact position indicator	Yes
Control type	Toggle
Local signalling	ON/OFF indication
Mounting support	DIN rail
9 mm pitches	4
Net weight	0.19 kg
Embedding depth	72 mm
Colour	White
Mechanical durability	20000 cycles
Electrical durability	20000 cycles conforming to IEC 61009
Connections - terminals	Tunnel type terminals1 cable(s) 10 mm ² flexible Tunnel type terminals1 cable(s) 16 mm ² rigid
Earth-leakage protection	Integrated

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Standards	EN/IEC 61009-1 EN/IEC 61009-2-1
Pollution degree	3 conforming to EN 61009
Overvoltage category	III
Tropicalisation	2 conforming to EN 61009
Relative humidity	95 % at 55 °C
Operating altitude	2000 m
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...60 °C

Packing Units

Package 1 Weight	0.201 kg
Package 1 Height	0.850 dm
Package 1 width	0.400 dm
Package 1 Length	1.000 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months
----------	-----------