



Main

Circuit breaker application	Distribution
Range	Acti 9
Product or component type	Earth leakage circuit breaker
Product name	DPN Vigî
Device short name	DPN N Vigî
Poles description	1P + N
Neutral position	Left
Number of protected poles	1
[In] rated current	32 A at 30 °C
Network type	AC
Trip unit technology	Thermal-magnetic
Curve code	C
Earth-leakage sensitivity	30 mA
Earth-leakage protection time delay	Instantaneous
Type	Type A-SI (Super Immunised)
Breaking capacity	6000 A Icn at 230 V AC conforming to EN 61009

Complementary

Device location in system	Outgoer
[Ue] rated operational voltage	230 V AC
Magnetic tripping limit	5...10 x In
Residual current tripping technology	Voltage independent
[Ics] rated service breaking capacity	6000 A at 230 V AC 50/60 Hz conforming to EN 61009
Limitation class	3 conforming to EN 61009
[Ui] rated insulation voltage	400 V AC conforming to EN 61009
[Uimp] rated impulse withstand voltage	4 kV conforming to EN 61009
Contact position indicator	Yes
Control type	Toggle
Local signalling	ON/OFF indication
Mounting support	DIN rail
9 mm pitches	4
Net weight	0.19 kg
Embedding depth	72 mm
Colour	White
Mechanical durability	20000 cycles
Electrical durability	10000 cycles conforming to IEC 61009
Connections - terminals	Tunnel type terminals1 cable(s) 10 mm² flexible Tunnel type terminals1 cable(s) 16 mm² rigid
Earth-leakage protection	Integrated

Environment

Standards	EN/IEC 61009-1 EN/IEC 61009-2-1
Pollution degree	3 conforming to EN 61009
Overvoltage category	III
Tropicalisation	2 conforming to EN 61009
Relative humidity	95 % at 55 °C
Operating altitude	2000 m
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...60 °C

Packing Units

Package 1 Weight	0.208 kg
Package 1 Height	0.750 dm
Package 1 width	0.360 dm
Package 1 Length	0.850 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months
----------	-----------